

Especificaciones

La foto es representativa

Eaton CPP4553

Eaton Crouse-Hinds series Arktite CPP plug, 7A/30A, 0.375-0.875" cable diameter, Two-wire, three-pole, Brass contacts, 60 Hz, Style 2, 0.5 HP/1.5 HP, Copper-free alum, Factory sealed, Delayed action circuit breaking, 125-250 Vac/480 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Arktite CPP plug
CATALOG NUMBER	CPP4553
UPC	782274175805
PRODUCT LENGTH/DEPTH	6.38 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	2.5 in
PRODUCT WEIGHT	1.175 lb



Especificaciones del producto

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2
SPECIAL FEATURES	Factory sealed
TYPE	Delayed action circuit breaking
AMPERAGE RATING	7A/30A
VOLTAGE RATING	125-250 Vac/480 Vac
CONTACT MATERIAL	Brass
CONFIGURATION	Two-wire, three-pole
FREQUENCY RATING	60 Hz
GROUNDING STYLE	Style 2

Recursos

CATÁLOGOS	Arktite CPS and CPP Explosionproof Receptacles and Plugs catalog page
GUÍAS DE ESPECIFICACIONES DE PRODUCTO	Eaton Specification Sheet - CPP4553
INSTRUCCIONES DE INSTALACIÓN	IF 285 - CPP Plugs
REPORTES DE CERTIFICACIONES	Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors Canadian certification

HORSEPOWER	0.50 hp, 1.50 hp
MATERIAL	Copper-free aluminum
CABLE DIAMETER	0.375-0.875 in

[Arktite CPS, CPP, CPR
Explosionproof Receptacles,
Plugs and Connectors UL
certification](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2025 Eaton. Todos los
derechos reservados.

Eaton es una marca registrada.

Todas las demás marcas
comerciales son propiedad de sus
respectivos propietarios.

Follow us on social media to get the latest
product and support information.

